

FA 48-O-CL-IDA-58-EX-AN

Product Description



The FA 48-O-CL-IDA-58-EX-AN provides high-quality Ethernet connectivity, enabling ISPs to offer the best service to their customers at a competitive price.

The 48-O-CL-IDA-58-EX-AN product features include:

- Supports EIRP of 36 dBm, with Tx power of 8 dBm, and antenna 28 dBi.
- Supports full range of services, up to 4 T1/E1 + Ethernet (Maximum 18 Mbps net throughput)
- Range of up to 80 Km
- Compatible with all FA4800 IDU devices and PoE device
- Hub site synchronization
- High quality TDM + Ethernet traffic over a single platform
- Robust interference-mitigation for license-exempt bands
- Automatic Adaptive Rate for optimal performance in all environments



FA 48-O-CL-IDA-58-EX-AN

Product Specifications

Architecture	Outdoor Unit (ODU); requires antenna. PoE or IDU required for network connectivity.
IDU to ODU Interface	Outdoor CAT5e cable; Maximum length: 100m total
Radio	
Frequency Bands	5.825 - 5.875 GHz
Data Rate	Up to 48 Mbps air interface, 18 Mbps Ethernet Throughput
Channel Bandwidth	Configurable: 5, 10, 20 MHz
Duplex Technique	TDD
Modulation	OFDM - BPSK/QPSK/16QAM/64QAM
Max Tx Power	Configurable in 1 dB steps, from 4 to 16 dBm
Received Dynamic Range	>60dB
Error Correction	FEC k=1/2, 2/3, 3/4
Management	
Protocol	SNMP based
Network Management	SNMPc based
Upgrade Capabilities	Local and remote 'over the air' software upgrade
Mechanics	
Dimensions	24.5cm(H) x 13.5cm(W) x 4.0cm(D)
Weight	1.0kg/2.2lbs
Power Feeding	From IDU or PoE device
Power Consumption	< 10W
Mounting	Pole and Wall
Environmental	
Outdoor Unit Enclosure	All weather case
ODU Operating Temperatures	-35°C to +60°C
Humidity outdoor unit	Up to 100% non-condensing
Antenna (example)	
Ext. Antenna 2ft (not included)	Other antennas available
Gain	28 dBi
Beam Width	4.5°
Polarization	Linear
Regulation	
FCC: 47CFR	Part 15, Subparts C&B
Safety	
UL	60950 (Third Edition)
EN	60950-1 (2001), IEC 60950-1 (2001)
CAN/CSA	C22.2 No. 60950
EMC	
FCC	CFR47 Class B, Part15, Subpart B
CAN/CSA-CEI/IEC	CISPR 22-02
EN	300 386 V1.3.2; 301 489-4 V1.3.1; 301 489-1 V1.4.1; 55022:1998; 61000-3-2:2000; 61000-3-3:1995; 55024:1998
AS/NZS	CISPR 22, CISPR 22:2002, CISPR 22:1997
Environmental	
ETSI	IEC 60721-3-4 Class 4M5 IP67